

ATTACHEMENT I

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford
		WELL NO: LBG-1
		PAGE 1 OF 1 PAGES
SITE LOCATION: Vineyard Point Road Guilford, CT		SCREEN SIZE & TYPE: SLOT NO.: SETTING:
DATE COMPLETED: November 18, 2010		SAND PACK SIZE & TYPE:
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SETTING:
DRILLING METHOD: Geoprobe		CASING SIZE & TYPE:
SAMPLING METHOD: Macro core		SETTING:
OBSERVER: J. Cassanelli		SEAL TYPE:
REFERENCE POINT (RP): Grade		SETTING:
ELEVATION OF RP: --		BACKFILL TYPE:
STICK-UP:		STATIC WATER LEVEL:
SURFACE COMPLETION:		DEVELOPMENT METHOD:
REMARKS: Refusal not encountered.		DURATION: YIELD:
GPS COORDINATES:		
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelly tube REC = recovery PPM = parts per million		

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	6	MC		4.3		0-0.3: Asphalt, sub-base. 0.3-4: SILT; little clay, little fine sand; red, soft.
	6					End of Boring.

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-2	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: Vineyard Point Road Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE:	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 5 ft bg.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelby tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	5	MC		5		0-0.5: Asphalt, sub-base. 0.5-5: SILT; little clay; little fine sand; red, soft.
	5					End of Boring.

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-3	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: Vineyard Point Road Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE:	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 5.5 ft bg.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelly tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	5.5	MC		4.6		0 - 0.7: Asphalt, sub-base. 0.7 - 4.6: SILT; little clay; little fine sand; red, soft.
	5.5					End of Boring

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-4	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: West Lane Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE: .	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 0.5 ft bg.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelly tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	0.5	MC				0 - 0.5: Asphalt, sub-base and organic topsoil.
	0.5					End of Boring.

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-5	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: West Lane Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE:	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 1.25 ft bg.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelby tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	1.25	MC		1.0'		0 - 0.4: Asphalt, sub-base. 0.4 - 1: SILT; little clay; little fine sand; red, soft.
	1.25					End of Boring.

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-6	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: West Lane Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE:	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 0.75 ft.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelly tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	0.75	MC		0.5		0 - 0.25: Asphalt, sub-base. 0.25 - 0.5: SILT; some clay; little fine sand; red, soft.
	0.75					End of Boring.

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. SHELTON, CONNECTICUT		OWNER: Town of Guilford	
		WELL NO: LBG-7	
		PAGE 1 OF 1 PAGES	
SITE LOCATION: Indian Cove Road Guilford, CT		SCREEN SIZE & TYPE:	
DATE COMPLETED: November 18, 2010		SLOT NO.: SETTING:	
DRILLING COMPANY: Connecticut Test Boring Seymour, CT		SAND PACK SIZE & TYPE:	
DRILLING METHOD: Geoprobe		SETTING:	
SAMPLING METHOD: Macro core		CASING SIZE & TYPE:	
OBSERVER: J. Cassanelli		SETTING:	
REFERENCE POINT (RP): Grade		SEAL TYPE:	
ELEVATION OF RP: --		SETTING:	
STICK-UP:		BACKFILL TYPE:	
SURFACE COMPLETION:		STATIC WATER LEVEL:	
REMARKS: Refusal at 1.5 ft.		DEVELOPMENT METHOD:	
GPS COORDINATES:		DURATION: YIELD:	
ABBREVIATIONS: SS = split spoon W = wash C = cuttings G = grab ST = shelby tube REC = recovery PPM = parts per million			

DEPTH (FEET)		SAMPLE TYPE	BLOW COUNT	REC. (FEET)	PID READING (PPM)	DESCRIPTION
FROM	TO					
0	1.5	MC		1.4		0 - 0.8: Asphalt, sub-base. 0.8 - 1.4: SILT; some clay, little fine sand; red, soft.
	1.5					End of Boring.